

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/043075 A1

(51) International Patent Classification⁷: **G01B 9/02**

(21) International Application Number:
PCT/FI2004/000639

(22) International Filing Date: 29 October 2004 (29.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20031581 30 October 2003 (30.10.2003) FI

(71) Applicant (for all designated States except US): **NOVEL-TECH SOLUTIONS OY** [FI/FI]; Tykistökatu 4, FI-20520 Turku (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KAUPPINEN, Jyrki** [FI/FI]; Kyypellontie 1, FI-21350 Ilmarinen (FI).

(74) Agent: **TURUN PATENTTITOIMISTO OY**; P.O. Box 99, FI-20521 Turku (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **INTERFEROMETER**



(57) Abstract: The present invention relates to an interferometer, comprising at least a beamsplitter (10), at least one end reflector (11) for returning beams (S2, S3), and a set of reflectors (14, 15) for reflecting the beams (S2, S3) between the beamsplitter (10) and the end reflector (11) or the end reflectors, at least some of said set of reflectors (14, 15) being adapted to be rotatable around an axis (w). Said set of reflectors comprises two angle reflectors (14, 15), constituted by plane reflectors, and the said end reflector (11) is or the end reflectors are an angle reflector constituted by plane reflectors (11', 11''). An angle line of the end reflector (11) is or the angle lines of end reflectors are arranged perpendicular to an angle line of both of the angle reflectors (14, 15).



WO 2005/043075 A1